

FLOWCOMMAND

UltraFlow™ Series

*Satellite connected and non-intrusive **flow meters** with ultrasonic sensing technology*



APPLICATIONS & BENEFITS

The FlowCommand UltraFlow system gives the power to measure and monitor fluid movement for an entire oilfield - all from any internet connected device. Example uses:

- Measure any oilfield fluid - raw streams, oil, wastewater, etc
- Monitor, measure and improve well production
- Reduce well downtime
- Track facility performance
- Improve equipment performance

FEATURES

UltraFlow sensors install easily, require no maintenance, and automatically send data to FlowCommand servers and software where it is accessible via any internet connected device:

- Instant installation that only requires a screwdriver
- Retains accuracy with wide variety of fluids and pipe sizes
- Advanced satellite telemetry built in
- Ultra efficient battery
- Intrinsically safe & non-incendive



DESCRIPTION & COMPONENTS


The UltraFlow system combines a sonic-based flow meter with a communications module to allow oil and gas operators to measure and transmit flow information from remote locations. There are three physical components to this system: (1) a main CPU module with battery and satellite transmitter, (2) an ultrasonic transducer, and (3) a solar panel to provide power.

UltraFlow gives operators the power to know exactly what is happening with flow streams from any well, facility, pipeline by allowing the tracking of any pipe-contained fluid movement with unprecedented ease, accuracy, and flexibility.

As with all FlowCommand products, no additional equipment or expertise is needed to start bringing your oil field online. UltraFlow installs with zero pipe intrusion, zero external power, and zero telemetry or SCADA system are needed. This is made possible by a number of breakthroughs and innovations pioneered by FlowCommand.

TECHNOLOGY INVOLVED

The primary mechanism for reading activity in the pipe is through the ultrasonic acoustic waves sent and received by the transducer. These waves are powerfully transmitted through the pipe wall, any scaling or paraffin buildup, and reflect off of the many bubbles, gas or solids present in the flowstream.



The proprietary onboard processor performs a spectral frequency analysis of the waves to calculate a flow profile. From the profile of these sound waves, a mix of on-board and cloud-based algorithms compute a fluid velocity in the pipe.

Unlike most sonic-based metering systems that require significant amounts of external power, UltraFlow uses algorithms to intelligently and dynamically manage its power system; this system allows the sensor to automatically manage its own power usage and supply merely with a solar panel the size of a tablet. And as with all FlowCommand sensors, the UltraFlow series sensors collect relevant data throughout the operation and sends it to cloud based software via satellite.

ADDITIONAL OPTIONS

- UltraFlow comes bundled with access to FlowCommand software that will automatically deliver daily reports and customizable alarms to notify recipients when a flow stream may be behaving unusually (well going down, etc).



- The CPU module in UltraFlow has the capability to read and transmit data from any piece of equipment with a HART or modbus output protocol
- UltraFlow can be paired with VoluSense tank monitoring solutions to allow operators to monitor their entire field from a computer in the office

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	
ACCURACY	
Measurement type	Proprietary ultrasonic based frequency-shift and transit-time algorithmic evaluation
Pre-calibration accuracy	5% ± 2.5%**
Repeatability	0.5% ± 0.25%**
Calibration Process	Provide to FlowCommand an approximate figure of the average flowrate of the target flow stream, the system then requires 36 hours to accumulate data
Post-calibration accuracy	2.5% ± 1%**
Measurement parameters	Velocity, volumetric, and totalized flow
Fluid types	Fluids with particulates or bubbles of 100 microns or larger and minimum concentrations of 75 ppm
Flow rate range	0.03 to 25 m/sec
TELEMETRY & COMMUNICATION	
Type	Satellite (with GSM bands as available option)
Direction	Uplink and downlink (down accessible only by FC personnel)
Latency	~30s
Frequency	~5 - 100/day standard
Power requirements	None (all supplied by included solar panel)
Inputs	4-20mA, HART, Modbus/RS485
Outputs	HART, Modbus/RS485, MicroUSB, sat-modem
ELECTRICAL SPECIFICATION	
Battery size	10,000 mAh
Expected operating time (without power)	200 hours
Solar panel peak power	12 watts
Solar panel peak voltage	17.0 V
Safety mechanism	Intrinsically safe barrier
Transducer cable	20 ft (6m), shielded coaxial pair
Total Number of cable inlets	2
MECHANICAL SPECIFICATIONS	
Components	CPU enclosure, solar panel, transducer, cabling, mounting-clamps
Pipe size range	1/2" to 180" (12.5 mm to 4.5 m) ID
Pipe material requirements	Carbon steel, stainless steel, ductile iron, copper, FRP, or any other that sufficiently conducts sound
Contact temp range	-40°F to 300°F (-40°C to 150°C)

Operating ambient temp range	-28°F to 180°F (-30°C to 80°C)
Mounting style (CPU)	Clamp-on
Dimensions (CPU)	193.80 x 117.60 x 78.49 mm (7.63 x 4.63 x 3.09 in.)
Mounting style (Solar Panel)	Clamp-on
Dimensions (Solar Panel)	220 x 255 x 5mm (8.7 x 10.1 x 0.2 in)
Mounting style (Transducer)	Clamp-on
Dimensions (Transducer)	85 x 35 x 38mm (3.375 x 1.375 x 1.5 in)
Aggregate weight	4.2 lbs
Enclosure materials	Polycarbonate and aluminum weather-proof
Couplant	High temperature resistant hydrophobic gel
Rating specification	Class I, Division 2, Group D with Class 1, Division 1 sensor port

*** accuracy and repeatability based on field proving test conditions; accuracy and repeatability may vary depending on fluid type, sensor placement, flow velocity, and other various factors*

FlowCommand Inc.

10606 Hempstead Rd Suite 112

Houston, TX 77092

T +1 775 773 5692

T +1 713 714 5547

sales@flowcommand.com

www.flowcommand.com

© 2019 FlowCommand Inc. All Rights Reserved.

Specifications are subject to change without notice. FlowCommand is a registered trademark of FlowCommand Inc. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with FlowCommand Inc.

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. Standard Terms and Conditions of Sale can be issued by contacting FlowCommand Inc. We reserve the right to modify or improve the designs and specifications of our products at any time without notice. FlowCommand Inc accepts no responsibility for any errors that may appear in this publication.



FLOWCOMMAND